



# BISTAR

TP6L60M  
TP6L60M(H) **120-cell**

350 - 370W

9BB Half-cut Mono Perc  
Full Black




## SYSTEM & PRODUCT CERTIFICATES

- IEC 61215 / IEC 61730 / UL 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational Health and Safety Management Systems



## PERFORMANCE WARRANTY



## KEY FEATURES



### 9BB Half-cut Cell Technology

New circuit design, lower internal current, lower Rs loss  
Ga doped wafer, attenuation <2% (1st year) / ≤0.55% (Linear)



### Significantly Lower the Risk of Hot Spot

Special circuit design with much lower hot spot temperature



### Excellent Anti-PID Performance

2 times of industry standard Anti-PID test



### Wider Application

No water-permeability and high wear-resistance,  
can be widely used in high-humid, windy and dusty area



### IP68 Junction Box

High waterproof level

## ELECTRICAL CHARACTERISTICS

Testing Condition	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum Power (Pmax/W)										
Operating Voltage (Vmpp/V)										
Operating Current (Impp/A)										
Open-Circuit Voltage (Voc/V)										
Short-Circuit Current (Isc/A)										
Module Efficiency (%)					19.70		20.00		20.30	

STC: Irradiance 1000W/m<sup>2</sup>, Spectral AM1.5, Module Temperature 25°C, Power output tolerance: 0~+5W, Test uncertainty for Pmax: ±3%  
 NMOT: Irradiance 800W/m<sup>2</sup>, Spectral AM1.5, Ambient temperature 20°C, Wind speed 1m/s

## MECHANICAL CHARACTERISTICS

Cell Type	Monocrystalline Silicon (9 Busbar)
No. of Cells	120 cells in series (6*20)
Module Dimensions	1755*1038*35mm (69.09*41.87*1.38 inches)
Weight	19.5kg (42.99 lbs)
Front Glass	
Frame	Anodized Aluminium Alloy
Junction Box	IP65, 3 Bypass Diodes
Output Cable	4mm <sup>2</sup> (IEC), 12AWG(UL) 300mm in Length Customized Length
Connectors	T01-LJ0-3-CS/M4/MC4-EV02

## I-V CURVE

TP6L60M/365W

Voltage (V)

## APPLICATION CONDITIONS

Maximum System Voltage	1000V/1500VDC
Operating Temperature	-40°C~+85°C
Maximum Series Fuse	20A
Safety Protection Class	Class I

Voltage (V)

## TEMPERATURE CHARACTERISTICS

Temperature Coefficient of Pmax	
Temperature Coefficient of Voc	
Temperature Coefficient of Isc	
Nominal Module Operating Temperature(NMOT)	

## TECHNICAL DRAWINGS

## PACKING CONFIGURATION

Pieces Per Pallet	
Pieces Per Container(40'HQ)	



Th